# Avtron AV485 SMARTach<sup>TM</sup> III Encoders



Severe Mill Duty Magnetic Encoder; Foot or NEMA 56C Face Mount, 5/8" Solid Shaft

### Magnetic Durability in a Compact Encoder

Severe Mill DutyUp to 50000 PPR

Replaces Competitive Models Without Rewiring

Self-Diagnostic LED & Alarm Output

Foot or NEMA 56C Face Mount Removable SensorsIP66 Enclosure

> High-Power Output Standard Outputs Fully Short Circuit Protected


Optional Dual Isolated Outputs

1 Year No-Hassle Warranty

#### AV485

The AV485 is designed to withstand the worst environments: buried in slag, coated in pulp, sprayed with salt water or cutting coolants, it keeps working. The modular, gull-winged design makes it easy to install and service; the base can be bolted in place without removing the encoder, and the AV5 wide-gap removable sensors require no adjustment or shimming. The sensors are fully potted to protect against liquids, and are interchangeable between AV850, AV485, and AV685 encoders. The universal 5-24V design drives longer cables and is protected against wiring errors and surges. A second backup output is available with the same or different PPR, and offers completely separate electronics for maximum uptime.

#### **OUTLINE DRAWING**





# **MORE AV485 SPECIFICATIONS**

Operating Power: Volts: 5 - 24 VDC\* Current: 100mA nom, no load Output Format: A Quad B with Marker (A, /A, B, /B, Z, /Z) Second Isolated Output: Optional Frequency Range: @5V, @1m cable, 250 kHz Max @24V, @300m cable, #8 output, 45 kHz Max Maximum Cable Length: 1000' PPR: 4 - 50000\*\* Speed: 5000 RPM Max\*\*\*\* Electronics: Fully Encapsulated, IP67\*\* Temperature: -40° to 120°C\* (150°C rotor)^ Vibration: 18 g's Shock: 1 meter drop test Chemical: Polyurethane enamel paint protects against salt spray, mild acids, and bases Weight: 14 lbs. [6.4 kg] / 16 lb [7.3 kg] dual output

\* Electrical specifications for SMARTach III model (serial #30,000 or higher), consult Nidec Industrial Solutions for earlier model specifications.

\*\* Certain connector options may reduce IP rating.

\*\*\*(PPR) Standard maximum PPR is 5000. Consult Factory with your application for PPRs up to 50,000. \*\*\*\* (Speed) Maximum RPM may be limited for PPR > 2,500. Consult Factory with

your application. ^ -20°C to 80°C Standard, requires high-temperature model and instrument air feed

for 120°C rating

All dimensions are in inches [millimeters].

Specifications and features are subject to change without notice.

Check out our website for more detailed specifications, drawings, and installation instructions. www.avtronencoders.com

# **SELECTION GUIDE**

## AV485NXS8LXXW000

MODEL	TEMPERATURE RATING	FOOT MOUNTING	SHAFT MOUNTING	LEFT OUTPUT LINE DRIVER	LEFT OUTPUT PPR	RIGHT OUTPUT LINE DRIVER	RIGHT OUTPUT PPR	CONNECTOR OPTIONS	MODIFICATIONS
AV485	N20°C to +80°C (Standard)	X - Standard NEMA 56C 4.5 in. Face Mount (No Foot Mount Included)		8 - 5-24v in, 5-24v out hi-power standard (HX)	L - 240 PPR	X - No Right Output	X - No Right Output	W - 36 in. Sealed Cable w/Color Coded Leads	000 - No Special Options



Nidec Industrial Solutions 243 Tuxedo Avenue - Cleveland, Ohio 44131 encoderhelpdesk@nidec-industrial.com +1 216-642-1230 - www.avtronencoders.com



Features and specifications are subject to change without notice. EU-SMART™, SMARTSafe™, SMARTTach™, THIN-LINE™, WIDE-GAP™, SAFETach™, and BULLSEYE32™ are trademarks of Nidec Industrial Solution. All other trademarks and registered trademarks are the property of their respective owners. Nidec Industrial Solutions' standard warranty applies. All dimensions approximate.